



CAMLOCKS RADIAL

Camlock Radial 16mm - 1 pull**KS03**

- One pull key removal
- 19mm Barrel diameter
- Supplied with 2 radial keys

**Camlock Radial 16mm - 2 pull****KS04**

- Two pull key removal
- 19mm Barrel diameter
- Supplied with 2 radial keys



KEY BOXES AND ACCESSORIES

Key Box Slim Double Pole On/Off**KB03**

- Radial key switch, on/off, opposing double poles
- Key removable in the on and off positions
- Slimline key box (25mm) for easy installation on narrow doorframes
- On/off LED indication
- Facility for company decal
- Tamper switch, spacer, screws and wall anchors provided
- Supplied with 3 radial keys

**Key Box Slim Spring Loaded****KB05**

- Radial key switch, springloaded, opposing double poles
- Slimline key box (25mm) for easy installation on narrow doorframes
- On/off LED indication
- Facility for company decal
- Tamper switch, spacer, screws and wall anchors provided
- Supplied with 3 radial keys

**Key Box Slim Spring Loaded Key Alike****KB06**

- Radial key switch, springloaded, opposing double poles
- Slimline key box (25mm) for easy installation on narrow doorframes
- On/off LED indication
- Facility for company decal
- Tamper switch, spacer, screws and wall anchors provided
- Supplied with 3 radial key-alike 3026 keys

**Key Box Slim On/Off Key Alike****KB06-1**

- Radial key switch, on/off, opposing double poles
- Key removable in the on and off positions
- Slimline key box (25mm) for easy installation on narrow doorframes
- On/off LED indication
- Facility for company decal
- Tamper switch, spacer, screws and wall anchors provided
- Supplied with 3 radial key-alike 3027 keys



KEY BOXES AND ACCESSORIES**Key Box Standard Double Pole On/Off****KB07**

- Radial key switch, on/off, opposing double poles
- Key removable in the on and off positions
- Key box dimensions: 92mm x 50mm x 54mm
- On/off LED indication
- Facility for company decal
- Tamper switch, spacer, screws and wall anchors provided
- Supplied with 3 radial keys

**Key Box Standard Double Pole Spring Loaded****KB09**

- Radial key switch, springloaded, opposing double poles
- Key box dimensions: 92mm x 50mm x 54mm
- On/off LED indication
- Facility for company decal
- Tamper switch, spacer, screws and wall anchors provided
- Supplied with 3 radial keys

**DAYLIGHT SWITCHES****Day / Night Switch 220VAC****SW12**

- 220-240VAC 50Hz Operating voltage
- 15A Maximum current capability
- Switching light level: 60 lux approx.

**Day / Night Switch 12VDC****SW12-1**

- 12VDC Operation
- Potential free relay contact N/O and N/C, 5A @ 12VDC
- Built in delay: 20s drop out

