

> ACCESS CONTROL READERS AND KEYPADS

RFID Reader 1000 Users

- RFID card/tag reader
- 1000 Users
- 12 - 24V AC or DC
- Uses LK142 tag or LK143 card
- Programmed with LK190-1 remote control
- Dimensions : 90 x 44 x 19mm
- Outdoor or indoor - IP65

LK190



SECURI-PROD

IR Remote Control

- For programming LK190
- Add/delete users on LK190
- Configure LK190

LK190-1



SECURI-PROD

Keypad/RFID Reader 1000 + 10 Users Slim-Line

- RFID card and/or PIN code
- 1000 Users (Relay1) + 10 Users (Relay2)
- 12 - 24V AC or DC
- Uses LK142 tag or LK143 card
- Metal housing
- Slim-line
- Dimensions : 152 x 45 x 25mm
- Outdoor or indoor - IP65

LK191



SECURI-PROD

Keypad/RFID Reader 1000 + 10 Users 4x3 Layout

- RFID card and/or PIN code
- 1000 Users (Relay1) + 10 Users (Relay2)
- 12 - 24V AC or DC
- Uses LK142 tag or LK143 card
- Metal housing
- Dimensions : 76 x 120 x 22mm
- Outdoor or indoor - IP65

LK192



SECURI-PROD

Keypad 1000 + 10 Users

- PIN codes
- 1000 Users (Relay1) + 10 Users (Relay2)
- 12 - 24V AC or DC
- Black plastic housing
- Dimensions : 118 x 76 x 22mm
- Outdoor or indoor - IP65

LK193



SECURI-PROD

ACCESS CONTROL READERS AND KEYPADS

RFID Proximity Tag ISO Black

LK142

- 125KHz, EM4102 Standard
- Can be used with a variety of access readers
- Reading range: TAG - 50mm



RFID Proximity Card ISO Slim-Line

LK143

- 125KHz, EM4102 Standard
- Can be used with a variety of access readers
- Reading range: CARD - 70mm



ACCESS CONTROL SYSTEMS

SOLO Controller Flush and Surface Mount

LK163

- Standalone access control unit
- Up to 50 tag users
- Single potential free relay output
- Door sense and free exit inputs
- Door timer function for alarm open and forced



LATTICE Controller V1 Flush and Surface Mount

LK160

- Standalone / network connected controller head
- 1000 user tag capacity
- Up to 31 slave readers on network
- 2 Output channels - potential free relay plus open collector output
- Free-exit input plus door-sense input
- PC interface via the take-up reader and Latticeware software(LK160-2)



LATTICE Slave Head Flush and Surface Mount

LK160-1

- Slave head for Lattice Controller (LK160)
- 1000 user tag capacity
- Up to 31 slave readers on network
- 1 Output channels - potential free relay plus open collector output
- Free-exit input plus door-sense input
- PC interface via the take-up reader and Latticeware software (LK160-2)

