

## ACCESS CONTROL SYSTEMS

### LATTICE Take Up HD and Latticeware

- PC interface for LATTICE controller
- Card enrolment at PC
- Easy management and configuration of LATTICE event logs

LK160-2



### Zaptag Grey Single Unit

- Tag for LATTICE/SOLO access control systems

LK161



### SOLO/LATTICE Rain Shield

- Rain shield for SOLO/LATTICE
- Stainless steel

LK162



## KEYLESS ACCESS KEYPADS

### SMARTGUARD Keypad 1000 Codes

LK91

- Standalone keypad for cost effective keyless access control
- 12 to 24VAC / DC
- Up to 1000 unique 1-10 digit codes
- 1 Relay output (pulsed or latched)
- Fully programmable via front panel
- Various panic conditions, including duress and panic
- Stainless steel rain shield for SMARTGUARD keypad Part No. LK90-2



LK91



LK90-2



## KEYLESS ACCESS KEYPADS

### SMARTGUARD Air Wireless Keypad – Black

LK91-7

- Completely wireless access keypad
- 1000 unique codes 1 – 10 digit codes
- 15 channel output (activate up to 15 devices)
- Up to two years of battery life with up to 300 uses per day
- Operating range of up to 30m
- Compatible with all CENTURION rolling code receivers
- Selective access downcounter for limited access to selected users



### KEYPRO Keypad 8 Codes

LK54

- Double-relay keypad in durable, weatherproof housing
- 4 - 13 Digit access codes for 8 users
- Codes can be issued for temporary access
- Wrong code lockout
- 2 Relays and anti-tamper switch
- Programmable panic facility



### Keypad Tamper Proof

LK92

- Prevents tampering or hot wiring of relay
- 12VDC or 24VAC operation
- Programmable master code with 6 user codes
- Relay time programmable in seconds or latch mode
- Power and relay LED indication
- Weatherproof housing



### NiceMoon Wireless Digi Keypad and 2 Channel Receiver

LK12-2

- Wireless access keypad including a 2 channel receiver
- Battery operated, 6VDC lithium batteries
- 433MHz rolling code technology
- 35m Indoor and 200m outdoor range
- IP54 Backlit, toned keypad with auto-shutdown



### Keypad Vandal Resistant 99 User E-PAD

LK10

- Operating voltage 12-24VAC / DC
- Alarm output relay N/O and N/C, 100mA
- Max 99 user codes, selectable 4 to 8 digits
- Weather resistant IP65 rating
- Lock and auxiliary relay rating 3A at 15VDC

