

POWER SUPPLIES AND ACCESSORIES

Power Supply 13.6VDC 3 Amp Power Store
PS49-1

- Output voltage: 13.6VDC 3 Amp
- Input voltage: 190-265VAC - 50-60Hz
- Lockable enclosure, grey epoxy coated finish
- Output short-circuit protection
- With SA plug top and 300mm lead
- Metal housing dimensions : 203mm (H) x 163mm (W) x 74mm (D)
- With battery back-up 7AH (Battery supplied separately)


Power Supply 13.6VDC 5 Amp Power Store
PS49-2

- Output voltage: 13.6VDC 5 Amp
- Input voltage: 190-265VAC - 50-60Hz
- Lockable enclosure, grey epoxy coated finish
- Output short-circuit protection
- With SA plug top and 300mm lead
- Metal housing dimensions : 295mm (H) x 198mm (W) x 90mm (D)
- With battery back-up 17AH (Battery supplied separately)


Power Supply Access Control 12VDC 3 Amp Power Store
PS49-3

- Output voltage: 12VDC 3 Amp with timer board
- Input voltage: 190-265VAC - 50-60Hz
- Adjustable timer 1 - 10 sec
- Lockable enclosure, grey epoxy coated finish
- Output short-circuit protection
- With SA plug top and 300mm lead
- Metal housing dimensions : 203mm (H) x 163mm (W) x 74mm (D)
- With battery back-up 7AH (Battery supplied separately)


Power Supply Access Control 12-14VDC 3 Amp
PS49-4

- Output voltage: 12 - 14VDC (adj) 3A
- Input voltage: 100 - 240VAC 50-60Hz
- Separate output for electronic lock (N/O and N/C)
- Push button input for lock release
- Adjustable lock time (1-10sec)
- Output short circuit protected
- Metal housing dimensions: 162mm (H) x 163mm (W) x 47mm (D)
- With SA plug top and 300mm lead


Power Supply 13.6 VDC 3 Amp
PS62-1

- Output voltage: 12-15VDC adjustable
- Output current: 3 Amp
- Input voltage: 100-240VAC - 40-60Hz
- Lockable enclosure, grey epoxy coated finish
- Fuse and lightning protection (by MOV)
- With plug and 500mm lead
- Metal housing dimensions: 165mm (H) x 165mm (W) x 50mm (D)




POWER SUPPLIES AND ACCESSORIES

Enclosed Power Supply CCTV 12VDC 10 Amp

PS70

- 12VDC 10 Amp switch mode power supply
- Input Voltage 175 to 265VAC @ 50Hz
- 1 x 10 Amp Output @ 12VDC
- Metal cage
- Dimensions : 199mm(L) x 98mm(W) x 38mm(H)
- This power supply must be housed in a suitable enclosure with ventilation



SECURI-PROD

Power Supply 16VAC 40VA 2.5 Amp

PS51

- Input voltage: 220VAC; 50Hz
- 16VAC 2A (40VA) output
- Standalone power supply with moulded lead and plug
- Terminal block for 16VAC connection
- Dimensions: 100mm (L) x 75mm (W) x 55mm (H)



SECURI-PROD

Power Supply 16VAC 50VA 3 Amp Protected

LT19

- Standalone transformer in housing with moulded plug and AC connector block
- 12/16VAC - 50VA, Output protected
- Input Voltage 220VAC - 50Hz
- Terminal block for 12 / 16VAC connection
- Dimensions: 125mm (L) x 72mm (W) x 63mm (H)



SECURI-PROD

PUSH BUTTONS AND SWITCHES

Securi-Prod No-Touch Sensor

SW165

- Input voltage: 12 VDC
- NO/NC contact
- Fits standard 4 x 2 box



SECURI-PROD

Securi-Prod Touch-to-Exit Sensor

SW165-5

- Input voltage: 12 VDC
- Touch to exit
- NO/NC contact
- Dimensions: (W) 56 x (H) 86 x (D) 20 mm



SECURI-PROD

Securi-Prod Slim-Line Push Button

SW168

- NO contact only
- Stainless steel finish
- Dimensions: (W) 30 x (H) 94 x (D) 17 mm



SECURI-PROD