

## ALARM ACCESSORIES - SIRENS AND SOUND DEVICES

### Motorised Siren 220V AC 500m

- IP44 Rating
- 220V - 0.5Amp Current
- 1 Minute maximum on
- Weather resistant ABS plastic design



SD12

### Motorised Siren 12V 1000m

- IP44 Rating
- 12V Siren - 7Amp current
- 1 Minute maximum on
- Weather resistant
- Metal design



SD09

### Motorised Siren 220V AC 1000m

- IP44 Rating
- 220V - 0.5Amp Current
- 1 Minute maximum on
- Weather resistant
- Metal design



SD11

## GSM COMMUNICATORS

### CENTURION 8 I/O Standalone GSM Module

- GSM module with 8 programmable optically isolated relay outputs (pulsed or latching)
- 8 Programmable optical isolated inputs (active low or active high)
- Operating voltage: 9 -12 VDC
- 5,000 User numbers
- Programmable temporary numbers for the control of: guest access, visitor access, maintenance and service technicians access
- Programmable via simple SMS commands or web portal
- Remote control of the inputs and outputs from anywhere in the world
- Pre-paid or contract SIM Cards
- Missed call (CLI), "please call me" or SMS in/output control with confirmed message structure message
- Remote airtime balance and recharge
- Signal strength indicator
- Unique web portal for easy programming and configuration
- Flash firmware updates (USB)



CP115-1



**GSM COMMUNICATORS****Sentry GSM Communicator****CP121**

- Standalone GSM or used in conjunction with Sentry GPRS server
- 2 Relay outputs
- 1 Digital output
- 2 Digital inputs
- Low power standby mode
- Programmable via USB (Intuitive application software)
- Real time clock/calendar with power backup
- Dual sim
- Status Indication LED (Tri-colour)
- Sim pin lock
- GPRS with SMS fail-over or SMS only
- 2 Master users
- 100 Regular users
- Input activation on high or low trigger

**SENTRY****2****CENTURION GSM Module 12V 2 Input / Output GSWITCH****CP116**

- Memory capacity of up to 300 numbers
- 2 Relay outputs, potential free, 1 Amp at 30VDC
- 2 Negative switching inputs
- Output pulse time 1ms - 50 days
- Supply voltage 12-24VDC

**CENTURION****SMS Alert 1 - 3 Input 1 Output 8 User****CP117-2**

- 3 Inputs, 1 x 10A output (1 = burglary, 2 = arm/disarm, 3 = panic).
- Reports to 8 users/cellphones.
- Recognizes up to 16 missed calls or unlimited missed calls, e.g. to be used as a gate opener.
- Waterproof enclosure.
- Pepper gas pulse function.
- Missed call to and from option.
- 12VDC, 40mA standby

**SMSALERT****SMS Alert 9****CP117**

- Includes 9 alarm inputs and 3 relay outputs
- Send SMS messages to end users
- 12 VDC
- Positive or negative trigger
- Pre-paid or contract
- Pulse or latch input
- Programmable messages

**SMSALERT**

## > GSM COMMUNICATORS

### SMS Alert Alarm

CP117-1

- Includes 9 alarm inputs
- 1 Switched relay, LED and siren output device
- Send SMS messages to end users
- 12 VDC
- Positive or negative trigger
- Pre-paid or contract
- Pulse or latch input
- Programmable messages
- Standalone system
- Key switch or SMS operated
- Siren and LED outputs



SMSALERT

## > PEPPER GAS ALARMS AND ACCESSORIES

### Pepper Gas Skunk Stand Alone Alarm 1

CP126

- Metal epoxy coated housing
- 1 X 225ml pepper canister (Natural pepper spray mixture)
- Remote arming (Code hopping up to 36 remotes) or a key switch
- No entry/exit delay warning from unit
- 12VDC 1.3Ah sealed lead acid battery back-up (2 days back-up period) solar charger input
- Passive input
- Max 30w siren output
- LED indicator for arming/disarming and for charging
- Up to 5 x 4 second spray time



### Pepper Gas Skunk Master Unit

CP127

- Pepper spray alarm system includes 1 x passive, control card, 250g canister, 1 button code hopping remote and 16VAC power supply
- Built-in code hopping receiver for up to 16 remotes
- On / off input for key switch, keypad, receiver or other switching devices
- Normally open panic input for siren activation only
- Potential free alarm relay output NC / NO
- Connects up to 3 pepper gas slave units



### Pepper Gas Skunk Slave Unit

CP127-1

- Pepper gas alarm slave unit
- 12VDC Trigger input (from master unit)
- Selectable trigger delay 0-30 seconds via jumper
- 250g pepper gas canister

