

CCTV BALUNS AND HUBS

All in One Single Channel Passive Video Transceiver Balun Pack UTP

CC50

- Transfer 1ch analogue HD video over Cat5e/6 UTP cable
- No power required
- Real time transmission: 720P/1080P video signal



**UTEPO
HD**

Video			
Transmission Distance (recommended)			
HDCVI	HD-TVI	AHD	Analogue Video
720P:370m 1080P:100m	720P:200m 1080P:200m	720P/960P:330m 1080P:330m	500m

Balun 1 Channel Active Receiver

CC51-1

- Power supplied: 12VDC
- Terminal block: 2 pin for UTP cable, 2 pin for power supply,
- 1 pin for grounding
- Transmission distance up to 600 Meter working with passive transceivers
- Transmission distance up to 1200 Meter working with active transmitter
- Compatible with worldwide formats including PAL, NTSC
- Higher standard built-in surge and transient protection
- Super interference rejection



UTEPO

TO BE DISCONTINUED

Balun 1 Channel Active Transmitter

CC52-1

- Power supplied: 12VDC
- Transmission signal: 1 Vpp Composite video
- Terminal block: 2 pin for UTP cable, 2 pin for power supply,
- 1 pin for grounding
- Transmission distance up to 1200 Meter working with active receivers
- Compatible with worldwide formats including PAL, NTSC
- Higher standard built-in surge and transient protection
- Super interference rejection



UTEPO

TO BE DISCONTINUED

All in One 4 Channel HD Video Passive UTP Balun

CC48

- 4channel HD analogue video signal over Cat5e/6 cable
- No power required
- Real time transmission: 720P/1080P video signal

Video			
Transmission Distance (recommended)			
HDCVI	HD-TVI	AHD	Analogue Video
720P:400m 1080P:100m	720P:100m 1080P:2100m	720P/960P:300m 1080P:300m	500m



**UTEPO
HD**

CCTV BALUNS AND HUBS

Balun 4 Channel Active Receiver Hub**CC47-1**

- Power supplied: 12VDC
- Terminal block: 2 pin for power supply, 1 pin for grounding
- Transmission distance up to 1200 Meter working with active transmitter
- Transmission distance up to 600 Meter working with passive transceivers
- Compatible with worldwide formats including PAL, NTSC
- Higher standard built-in surge and transient protection
- Super interference rejection

**UTEPO*****TO BE DISCONTINUED*****Balun 16 Channel Passive Transceiver Rack Mount Hub****CC61-1**

- No power required
- Compatible with worldwide video formats including PAL, NTSC
- Transmission distance up to 300 Meter working with passive transceivers
- Transmission distance up to 600 Meter working with active receivers
- Built-in surge and transient protection
- Super interface rejection
- LWH: 430mm x 100mm x 45mm (19" with rack-mounting ears)

**UTEPO*****TO BE DISCONTINUED*****Balun 16 Channel Active Receiver Rack Mount Hub****CC60-1**

- Power supplied: 100-240VAC
- Compatible with worldwide formats including PAL, NTSC
- Transmission distance up to 1200 Meter working with active transmitter
- Transmission distance up to 600 Meter working with passive transceivers
- Higher standard built-in surge and transient protection and with grounding rod
- Super interference rejection
- LWH: 430mm x 95mm x 44mm (19" with rack-mounting ears)

**UTEPO*****TO BE DISCONTINUED***